Product data sheet Characteristics

47312

voltage release XF com - 48 V DC/AC 50/60Hz



		.9
Device short name	XF com	i.
Product or component type	Voltage release	2
Device application	Control	
Range compatibility	Masterpact NW Masterpact NT	for
[Uc] control circuit voltage	48 V AC 4860 V DC	Products

Complementary

Complementary		
Threshold tripping voltage	0.851.1 Un	eii ab
Supply holding power	4.5 W	
Mounting mode	Fixed	ab Jilio
Response time	70 ms Masterpact NW in 800 A	, no
	70 ms Masterpact NW in 1000 A	المان الم
	70 ms Masterpact NW in 1250 A	. <u></u>
	70 ms Masterpact NW in 1600 A	dete
	70 ms Masterpact NW in 2000 A	for
	70 ms Masterpact NW in 2500 A	. p
	70 ms Masterpact NW in 3200 A	90
	70 ms Masterpact NW in 4000 A	<u> </u>
	80 ms Masterpact NW in 4000 A	<u> </u>
	80 ms Masterpact NW in 5000 A	<u></u>
	80 ms Masterpact NW in 6300 A	and
	55 ms Masterpact NT	for

Contractual warranty

144 4 1	40 (1	
Warranty period	18 months	