



## Main

|                              |                                                                                                                                                                                                 |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device short name            | MN delay unit                                                                                                                                                                                   |
| Product or component type    | Time delay auxiliary                                                                                                                                                                            |
| Device application           | Control                                                                                                                                                                                         |
| Range compatibility          | Masterpact - Masterpact NW<br>Masterpact - Masterpact NT<br>Compact - Compact NSX<br>Compact - Compact NS630b...1600<br>Compact - Compact NS1600b...3200<br>PowerPact - PowerPact Multistandard |
| Offer type                   | C4<br>C5                                                                                                                                                                                        |
| Voltage release type         | Instantaneous                                                                                                                                                                                   |
| [Uc] control circuit voltage | 100...130 V AC 50/60 Hz<br>100...130 V DC                                                                                                                                                       |

## Complementary

|                                    |                                                                       |
|------------------------------------|-----------------------------------------------------------------------|
| Impulse duration                   | 200 ms                                                                |
| Time delay range                   | 0.5...3 s                                                             |
| Threshold tripping voltage         | 0.35...0.7 Un - during open time<br>0.85 Un - during close time       |
| Supply holding power               | 4.5 VA                                                                |
| Supply inrush power                | 200 VA                                                                |
| Response time                      | 0.5 s<br>0.9 s<br>1.5 s<br>3 s                                        |
| Accessory / separate part category | Spare part Compact NS630b...1600<br>Spare part Compact NS1600b...3200 |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|